

(18+1)×1 Multimode Pump & Signal Combiner (MMPC Series)

Rev 11

Features

- High Power Transfer Efficiency
- Wide Wavelength Range
- Proprietary Tapering and Package Technique
- Custom Configurations Available

Applications

- Fiber Lasers
- Fiber Amplifiers

Description


- Pump Combiner with Signal Feedthrough

Specifications

| Parameter | Unit | Value |
|---------------------------------------|------|-------------------------------------|
| Product Type | - | (18+1)×1 |
| Pump Wavelength Range | nm | 900 - 1000 |
| Signal Wavelength Range | nm | 1064 |
| Fiber Type for Input (Pump Channel) | - | Nufern 105/125 (0.15 NA or 0.22 NA) |
| Fiber Type for Input (Signal Channel) | - | 10/125 DC, NA = 0.08/0.46 |
| Fiber Type for Output | - | 30/250 DC, NA = 0.06/0.46 |
| Max. Input Pump Power | W | 18 × 10W |
| Signal Channel Insertion Loss | dB | < 0.70 |
| Typ. Signal Channel Insertion Loss | dB | 0.5 |
| Min. Pump Efficiency | % | 95 |
| Typ. Pump Efficiency | % | 97 |
| Package Dimensions | mm | 100 (L) × 15 (W) × 10 (H) |
| Operating Temperature | °C | - 5 to + 65 |
| Storage Temperature | °C | - 40 to + 85 |

¹Mode number summation of all input fibers should be less than that of output fiber.

Package Dimensions



Ordering Information

MMPC-(18+1)×1-①①-②②②-③③-④④-⑤⑤-⑥

①①: Signal Wavelength

06 - 1064 nm

SS - Specify

②②②: Pump Wavelength

915 - 915 nm

976 - 976 nm

SSS - Specify

③③: Fiber Type for Pump Input

15 - 105/125 (0.15 NA)

22 - 105/125 (0.22 NA)

SS - Specify

④④: Fiber Type for Signal Input

10 - 10/125 DC, NA = 0.08/0.46

SS - Specify

⑤⑤: Fiber Type for Output

30 - 30/250 DC, NA = 0.06/0.46

SS - Specify

⑥: Fiber Length

Q - 0.75 m

S - Specify