

Model Number: **EDFA-CW-L0-RS-35-30-FCA**

Product Code: **1511**

Micro Processor Controlled EDFA



Specifications:

Parameters	Specifications
Wavelength Range	1570 – 1610 nm, L-band single channel
Gain Flattening Filter	Not included
Output Power	+35 dBm, tested with 1590 nm, +5 dBm input
Gain	30 dB, tested with 1590 nm, +5 dBm input
Optical Input Fiber	900um loose tube, FC/APC, blue, 1 meter, SMF-28
Optical Output Fiber	900um loose tube, FC/APC, red, 1 meter, SMF-28
Input Power Monitoring Range	-10 dBm to +10 dBm
Output Power Monitoring Range	+16 to +36 dBm
Input Power Measurement Accuracy	≤ +/- 0.5 dB, 1590 nm
Output Power Measurement Accuracy	≤ +/- 0.5 dB, 1590 nm
Noise Figure	≤ 6.5 dB typical, tested at 30 dB gain, 1590 nm, +5 dBm input
Control and Communication Interface	RS-232, RS232 Voltage Level
Dimension	150 x 146 x 20.5 mm
Power Input	1 of +3.3 VDC +/- 5%, 1 A current capacity 4 of +2.5 VDC, 6.5 A current capacity,
Electrical Interface Connector	PN: 173-E25-113R001 Male 25-PIN
Operational Case Temperature Range	0 to +65 °C
Mode of Operation	AOPC (constant output power control), ACC (constant pump current control)



日本デバイス株式会社

www.j-device.com

E-mail sales@j-device.com

Tel 03-6262-3424 Fax 03-6800-5883

Proprietary Information of Nuphoton Technologies

Manufactured in the USA

info@nuphoton.com

+1-(951)-696-8366

+1-(951) 696-8394

Electrical connector:

Part number: 173-E25-113R001

Pin No.	Description	Pin No.	Description
1	+3.3V PWR IN	14	GROUND
2	+2.5V PWR IN1	15	GROUND
3	+2.5V PWR IN1	16	GROUND
4	+2.5V PWR IN2	17	GROUND
5	+2.5V PWR IN2	18	GROUND
6	+2.5V PWR IN3	19	GROUND
7	+2.5V PWR IN3	20	GROUND
8	+2.5V PWR IN4	21	GROUND
9	+2.5V PWR IN4	22	GROUND
10	Laser Enable/ Disable	23	CASE TEMPERATURE ALARM
11	COMMON ALARM	24	GROUND
12	RS232 TX	25	GROUND
13	RS232 RX		



日本デバイス株式会社 E-mail sales@j-device.com
www.j-device.com Tel 03-6262-3424 Fax 03-6800-5883



Proprietary Information of Nuphoton Technologies
 Manufactured in the USA