

1310nm 1W Fiber Coupled Laser Diode Module | Built-in TEC Cooler | 14-Pin Butterfly Package
1310nm 1W|14-PIN (BTF) Package| 105um 200um 400um Fiber Core| High Power LD | Built-in PD
WSLX-1310-001-M-H14-T-PD
Wavespectrum Laser Group
www.wavespectrum-laser.com


PARAMETER	SYMBOL	VALUE	UNIT
Reverse Voltage	V_r	2.0	V
Operating Temperature	T_{op}	+10 ~ +30	°C
Storage Temperature	T_{stg}	-20 ~ +80	°C
Lead soldering temperature (10 sec.)	T_{is}	260	°C

Features:

- 1310nm
- Multimode Fiber
- 14-Pin Package
- Built-in TEC Cooler
- Built-in Photodiode

Applications:

- Medical Laser Treatment
- Others



Specifications
WSLX-1310-001-M-H14-T-PD

	Min.	Type	Max.
Center Wavelength@25°C	±10nm	1310nm	±30nm
Spectral Width (FWHM)		8nm	
Output Power	-----	1W	-----
Temperature Coefficient of Wavelength		0.7nm / °C	
Threshold Current (Typ.)	-----	0.4A	0.7A
Operating Current (Typ.)	-----	3.3A	3.5A
Operating Voltage	-----	1.4V	1.6V
Recommended Case Temperature	25°C		
TEC Max. Current	2A		
TEC Max. Voltage	8V		
Thermistor	10K		
Fiber Core Diameter	105um (200um 400um Optional)		
Fiber Length	>80cm		
Connector Type	SMA905/ST/FC		
Package Style	14-Pin		
Photodiode	Built-in		

sales@wavespectrum-laser.com



14-Pin Package View:



Pin Out:

PIN	FUNCTION	PIN	FUNCTION
1	TEC(+)	14	TEC(-)
2	THERMISTOR	13	CASE
3	PD(+)	12	NC
4	PD(-)	11	LD(-)
5	THERMISTOR	10	LD(+)
6	NC	9	NC
7	NC	8	NC

Electrically shorten LD module and store in non-extreme conditions.
Suggest using the constant current power supply.

