

Key Features

- High output power up to 27 dBm
- Similar gain & noise figure as typical EDFA
- Lower power consumption compared to conventional Raman amplifier
- Distortion-free amplification



2U Rackmount Casing




Others

Description

Amonics' E-Band Bismuth-doped fiber amplifier (BDFAs) uses bismuth-doped fiber as the gain medium. The BDFAs feature high small signal gain and low noise figure. The silica-based Bismuth-doped fiber offers the similar fundamental advantages as erbium-doped fiber used for amplification in the C and L bands. The E-band BDFAs are available to fulfill the increasing bandwidth demands.

The turnkey microprocessor-controlled BDFAs provide illustrative alarms and status indicators. An integrated RS232 computer interface enables easy control, diagnostic functions and data acquisition. The BDFAs are available in both benchtop and rackmount casings.

Application



- Datacom Network



ISO 9001 : 2015
Certificate No.: CC 5346

Our product is manufactured under a HKQAA ISO 9001 certified quality management system. The ISO 9001:2015 certification applies to the Hong Kong production site only.

Specifications

Model	ABDFA-E-23	ABDFA-E-27
Operating Wavelength	1425 nm to 1465 nm	1425 nm to 1465 nm
Input Signal Level	-30 to 10 dBm	-6 to 6 dBm
Output Power @ 0 dBm input power, 1445 nm	Min. 23 dBm	Min. 27 dBm
Optical Gain @ -30 dBm input power	Min. 28 dB, Typ. 30 dB	-
Noise Figure @ 0 dBm input power	Typ. 6.5 dB, Max. 7.0 dB	Typ. 6.5 dB, Max. 7.0 dB @ 1445 nm
Input / Output Isolation	Min. 30 dB	Min. 30 dB
Control Mode	ACC, APC	ACC, APC

General Parameters

	Value
Operation Temperature	0 to +40 °C
Storage Temperature	-10 to +70 °C
Power Supply	90 – 240 VAC, 47 – 63 Hz
Dimensions	485(W) x 360(D) x 90(H) mm
Mechanical Safety Control	Key-lock switch, BNC interlock key
Optical Power Monitoring	Output power, Input power
Remote Control Port	DB-9 female (RS232), Control software included, RJ-45 (TCP/IP Ethernet) (optional)
Protection	Pump Power Protection
Optical Connector	FC/APC, FC/UPC, SC/APC, SC/UPC
Optical Fiber	SMF-28

Ordering Information

Product Code	ABDFA-E-aa-b-cc	aa : Saturation output power in dBm b : R for 19" Rackmount cc : FA for FC/APC, FC for FC/UPC, SA for SC/APC, SC for SC/UPC
--------------	-----------------	---

Amonics undertakes continuous and intensive product development to ensure its product performance at the highest technical standards. As a result, the specifications in this document are subject to change without notice.

Amonics Limited (Hong Kong)

14/F, Lee King Industrial Building, 12 Ng Fong Street,
San Po Kong, Kowloon, Hong Kong
Tel :+852 2428 9723 Fax :+852 2428 9704

Beijing Amonics Co. Ltd. (Beijing)

Room 902, Unit 1 Joy Mansion, NO.99 Chaoyang North Road, Beijing China 100123
Tel :+86 10 8478 3386 Fax :+86 10 8478 3396
Email: contact@amonics.com Website: www.amonics.com



日本デバイス株式会社 E-mail sales@j-device.com

www.j-device.com

Tel 03-6262-3424 Fax 03-6800-5883